

Soneplex®

Quad Loop Extender 3192 Adapter



ADC's Quad Loop Extender (QLX) 3192 shelf adapter is an adapter board that allows for an ADC Soneplex QLX module to be plugged into an industry-standard 3192 office repeater shelf. The QLX 3192 shelf adapter also supports an optional ADC System Controller Unit (SCU) for system management and craft port access. Using the QLX 3192 shelf adapter, an existing copper-based T1 repeater shelf can be converted into a fiber optic transport platform, enabling simple, cost-effective transition of a legacy network from copper to fiber without the need for expensive shelf upgrades, additional wiring or installation costs.

The QLX module converts four multiplexed DS1 signals into an optical DS2 for delivery over single-mode optical fibers. The optical DS2 is converted back to four DS1s at the customer premises. The QLX module utilizes two fibers and is available with either an FC or SC type connector. The SCU provides optional system management and craft port access. Together, the QLX 3192 shelf adapter, QLX module, and SCU module comprise a circuit pack occupying four slots in the standard 3192 chassis. Up to seven circuit packs can be used in the 3192 shelf supporting up to 28 DS1s per shelf. This solution is ideal for cellular backhaul applications or tenant services within business parks or shopping centers.

SPEC SHEET

Benefits

- Convert legacy 3192 office repeater housing/shelves into a cost-effective fiber optic transport platform
- Capitalize on your investment of existing 3192 shelves and wiring by simply replacing copper transport cards with QLX circuit packs for fiber transport
- Easy to use system management allows configuration, remote provisioning and circuit visibility that simplifies network management



Specifications

Mounting:	Industry-standard 3192 T1 repeater housing
Adapters per Chassis:	7 circuit packs comprised of 3192 adapter, QLX module and optional SCU module; supports up to 28 DS1s per shelf
Dimensions (HxWxD):	10.5" x 2.6" x 10.5" (26.7 x 6.6 x 26.7 cm) (maximum envelope)
Operating Temperature:	-40°F to 149°F (-40°C to 65°C)
Operating Humidity:	10% to 95%, relative humidity, non-condensing

Ordering Information

Description	Ordering Number
Soneplex Quad Loop Extender 3192 Shelf Adapter	QLX-3192A
Soneplex Quad Loop Extender Module with FC connector	QLX-FCA211
Soneplex Quad Loop Extender Module with SC connector	QLX-SCA211
Soneplex System Controller Unit	SPX-SCU0A42

SPEC SHEET



Web Site: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our web site.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

102692AE 4/06 Original © 2006 ADC Telecommunications, Inc. All Rights Reserved